



PIGMENTED

CONCRETE SEALER

INSECO's PIGMENTED CONCRETE SEALER is a premium, silicone acrylic, penetrating, concrete sealer. It penetrates into the surface and produces a tough, durable, water- repellent barrier.

The PIGMENTED CONCRETE SEALER is available in a variety of colors and protects against water, UV rays, most acids, industrial chemicals, oil and grease. It also provides tremendous resistance against wear from both foot and vehicular traffic.

Must Prep:
clean & dry
surface

2 thin coats
recommended

200-300 sqft
coverage/gal

Clean up
with xylene



HAGA CLIC AQUÍ PARA ESPAÑOL

Finish:	Sheen
Pigment Type:	Titanium Dioxide & Inert Pigments
Vehicle Type:	100% Acrylic Copolymer
Solvent Type:	Aromatic Hydrocarbons
% Solids By Weight:	46% +/- 2%
% Solids By Volume:	30% +/- 2%
Density:	9.4 lbs. per gallon
Viscosity @ 75 deg. F (24 deg. C):	80 +/- 2 K.U.
Coating VOC:	<600 g/l
Flash Point, Minimum:	107 deg. F
Clean Up:	Xylene
Estimated Dry Time:	
Touch: 30-60 Minutes Recoat: 2 Hours Foot Traffic: 24 Hours Vehicular Traffic: 72 Hours	

RECOMMENDED USES: For properly prepared driveways, garage floors, patios, walkways, pool decks, warehouse floors, pavers, brick, block, masonry walls and cement tile roofs.

SURFACE PREPARATION: Dirt, grease, grime and any foreign material must be removed before application of new coating. Treat surface for mildew. Oil and grease should be scrubbed with a solution of TSP and water. Be sure surface is clean and dry. Contact an INSECO representative for detailed surface preparation specifications.

New Concrete: Etch with one (1) part muriatic acid to four (4) parts water. After etching is complete, thoroughly wash with a solution of TSP and water or an alternate acid-neutralizing detergent and rinse with clean water. Allow to dry for a minimum of 24 hours before applying PIGMENTED CONCRETE SEALER.

Pre-Painted Surfaces: Do not acid etch. Check to insure existing coating is tightly adhered to the substrate. Always apply a test sample to ensure proper adhesion. The PIGMENTED CONCRETE SEALER may not adhere to alkyds, epoxies, urethanes or water-based coatings.

APPLICATION INFORMATION: Mix product thoroughly and apply with a solvent resistant brush, roller or airless sprayer. When spraying, use a tip designed for gloss coatings. Apply when surface and air temperatures are above 50 Deg. F. Do not apply if the threat of rain exists or if moisture or dew may condense on the surface prior to PIGMENTED CONCRETE SEALER curing. Cover and protect all vegetation and surrounding areas not being sealed. Do not over apply, soak the concrete or allow the product to puddle. Two thin coats are recommended for best performance. Coverage will average 150 to 300 square feet per gallon depending on texture and porosity of the surface. Clean up drips, spills, tools, and equipment with Xylene.

RECOMMENDED THINNER: PIGMENTED CONCRETE SEALER does not require thinning and should be used as is, directly from the container.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 200-300 square feet per gallon. Note: PIGMENTED CONCRETE SEALER complies with the 1999 AIM regulation category of Water Repellant Sealer that has a VOC limit of 600 g/l. Thinning of this product will render it noncompliant.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An Inseco representative should be contacted with any questions concerning product information or application procedures. Our products conform to Inseco quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

Environmental & Safety Information: Improper handling or use may be hazardous. Recommended safety precautions for storage, handling and application must be observed.

DANGER: COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN!

Contains flammable solvents. Causes eye burns. Vapor is harmful. May cause allergic skin reaction. Do not get in eyes, on skin or on clothing. Wear eye and skin protective equipment when handling. Wear appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable levels. Follow respirator manufacturer's recommendations for use. Keep containers closed when not in use. **First Aid:** In case of eye contact, flush eyes immediately with plenty of fresh water for at least 15 minutes. Call a physician. If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth and seek immediate medical assistance. In case of skin contact, wash immediately with soap and fresh water. Remove contaminated clothing and launder before use. Discard shoes if material has penetrated inside surface. Notice: Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



INSECO

Inseco, Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com