



SEALTHANE

NATURAL MATTE FINISH • 2 PART URETHANE SEALER

INSECO's SEALTHANE Natural Matte is a 2 part, aliphatic, water based, chemical resistant, acrylic urethane. It is an environmentally friendly, protective finish designed to seal and protect concrete and pavers. SEALTHANE Natural Matte penetrates into the surface and produces a tough, durable, clear film that will maintain the appearance of the surface. SEALTHANE Natural Matte exhibits a matte finish with very little color enhancement. SEALTHANE Natural Matte binds joint sand and protects against water damage, staining, UV ray damage and will not yellow. SEALTHANE Natural Matte also provides mildew protection and tremendous resistance against wear from both foot and vehicular traffic. SEALTHANE Natural Matte may be applied to damp surfaces which allows for same day cleaning and sealing.



[HAGA CLIC AQUÍ PARA ESPAÑOL](#)

RECOMMENDED USES: For use on Concrete Surfaces including Brick Pavers, Driveways, Garage Floors, Walkways, Patios, Slate, Saltillo Tile and Clay Roof Tile. Also may be used as a non-yellowing, clear sealer to protect decorative vinyl flakes on concrete floors.

SURFACE PREPARATION: Dirt, grease, grime and any foreign material must be removed before application of new coating. Treat surface for mildew. Oil and grease should be scrubbed with a solution of OxyClean and water or alternate degreaser. Contact an INSECO representative for detailed surface preparation specifications.

APPLICATION INFORMATION: Combine Part A & Part B and mix thoroughly with gentle agitation for 2-3 minutes. Do not whip air into the material. SEALTHANE Natural Matte has a 2-3 hour pot life once Part A & Part B are combined, therefore, do not mix more than you can apply in that time frame. Apply with brush, roller, airless sprayer or garden sprayer. When spraying, use a tip designed for gloss coatings. Apply when surface and air temperatures are above 50 Deg. F. Do not apply if the threat of rain exists or if moisture or dew may condense on the surface prior to SEALTHANE Natural Matte curing. Cover and protect all vegetation and surrounding areas not being sealed. Do not over apply, soak the substrate or allow product to puddle. Two thin coats are recommended for best performance. A second coat may be applied when the first coat is dry to the touch. Do not apply additional coats 36 hours after the first coat was applied.

MIX RATIO:

Maximum Performance: 4 Parts A 1 Part B 2 1/2 Parts Water	Standard Performance: 4 Parts A 1 Part B 5 Parts Water	Maximum Reduction: 4 Parts A 1 Part B 10 Parts Water
--	---	---

CLEAN UP: Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 300-400 square feet per gallon.

SEALTHANE is water based. Do not Freeze.

Finish:	Flat
Pigment Type:	None
Vehicle Type:	Acrylic Urethane
Solvent Type:	Water
% Solids By Weight:	50 % +/- 2%
% Solids By Volume:	48 % +/- 2%
Density:	8.80 lbs. per gallon
Viscosity @ 75 deg. F (24 deg. C):	Waterlike
Coating VOC:	< 100 g/l
Flash Point, Minimum:	Not Flammable
Flame Spread:	Class A rating on non combustible substratum
Estimated Dry Time:	Touch: 30-60 Minutes Recoat: 2 Hours Foot Traffic: 24 Hours Vehicular Traffic: 48 Hours

CAUTION: KEEP OUT OF REACH OF CHILDREN! WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Technical data contained here in is true and accurate at the date of issue, but is subject to change without notice. An Inseco representative should be contacted with any questions concerning product information or application procedures. Our products conform to Inseco quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.



INSECO

INSECO, Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com