



# SOLID WOOD Rx+

## SEALER, STAIN & WATER REPELLENT

Solid WOOD Rx + is a 100% acrylic solid color wood stain designed to effectively seal, protect and beautify wood and composite surfaces. Its specialized formula resists moisture penetration, mildew, water staining and uneven discoloration. Solid WOOD Rx + is designed for maximum performance in any climate. Solid WOOD Rx + is available in any color and produces a finish which is durable and easy to maintain. Solid WOOD Rx + is the best prescription for solid wood protection.

Self-Priming  
Protective  
Finish

May  
Apply to  
Wet or Dry  
Wood

Repels  
Water

Mildew  
& UV  
Resistance

Durable in  
All Climates

**RECOMMENDED USES:** For use on virtually all properly prepared, exterior wood surfaces such as decks, docks, sidings, specialty hardwoods, pressure treated lumber, garden furniture, playhouses, composite decking, siding and log/timber frame homes. Contact an INSECO representative for detailed specifications.

**SURFACE PREPARATION:** Dirt, grease, grime and any foreign material should be removed before applying.

Solid WOOD Rx +. Be sure surface is clean and dry.

1. Apply a solution of 1 part household bleach or bleach alternative, 1 part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants.
3. Apply a test sample of Solid WOOD Rx + to insure proper adhesion and an appealing appearance. If beading or crawling occurs, contact INSECO prior to applying.

**Note:** When applying a Solid WOOD Rx + stain to new or uncoated wood, there is a possibility that tannin stains may appear. Certain wood types and colors may be more susceptible to tannin stains than others. Please contact INSECO to learn more regarding tannin staining and how to prevent or minimize it.

#### APPLICATION:

1. Stir Solid WOOD Rx + thoroughly before use.
2. Apply with a brush, roller or airless sprayer
3. Apply 1-2 coats as required to achieve a uniform appearance. Two coats are recommended for maximum performance. Allow 2-4 hours between coats.
4. Solid WOOD Rx + may be applied to damp or dry wood.

**RECOMMENDED THINNER:** Solid WOOD Rx + does not require thinning and should be used as is, directly from the container.

**CLEAN UP:** Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

**COVERAGE (THEORETICAL):** Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 200-400 square feet per gallon. Two coats are always recommended for maximum performance.

#### RESISTANCE TO:

Weather/UV : Excellent  
Moisture Penetration : Excellent  
Peeling/Flaking/Blistering : Excellent  
Mildew : Excellent



**INSECO**

INSECO, Inc.  
2897 South Street  
Fort Myers, FL 33916

[insecoproducts.com](http://insecoproducts.com)  
(800) 883-5150  
[info@insecoproducts.com](mailto:info@insecoproducts.com)



HAGA CLIC AQUÍ PARA ESPAÑOL

Finish:	Satin
Pigment Type:	Titanium Dioxide & Inert Pigments
Vehicle Type:	100% Acrylic
Solvent Type:	Water
% Solids By Weight:	49% +/- 2%
% Solids By Volume:	35% +/- 2%
Density:	10.72 lbs. per gallon
Viscosity @ 75 deg. F (24 deg. C):	105 +/- 2 K.U.
Coating VOC:	Less than 150 g/l
Flash Point, Minimum:	Not Flammable
Flame Spread:	Class A rating on non combustibile substratum
Estimated Dry Time:	Touch: 30-60 minutes Recoat: 2-4 hours Foot Traffic: 24 hours

**Do not apply if the threat of rain exists. Keep from freezing.**

**CAUTION: KEEP OUT OF REACH OF CHILDREN! WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Technical data contained here in is true and accurate at the date of issue, but is subject to change without notice. An Inseco representative should be contacted with any questions concerning product information or application procedures. Our products conform to Inseco quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.