

FORMULATED FOR PLANTATION SHUTTERS

SHUTTER COAT



SHUTTER COAT is an acrylic/hybrid, waterborne enamel specially formulated for plantation shutters. SHUTTER COAT will not raise the grain of the wood and dries quickly to a smooth, hard finish. While originally developed for plantation shutters, SHUTTER COAT offers exceptional performance on all types of millwork including cabinets, doors, furniture moldings and trim.

Shutter Coat is designed for spray application.

Cabinets

Doors

Furniture

Molding & Trim



HAGA CLIC AQUÍ PARA ESPAÑOL

RECOMMENDED USES:

Developed for plantation shutters and all types of mill work including cabinets, doors, furniture moldings and trim.

SURFACE PREPARATION:

Dirt, grease, grime and any foreign material should be removed before application of SHUTTER COAT. Ensure surface is clean and dry. Contact an INSECO representative for detailed surface preparation specifications.

APPLICATION INFORMATION:

Mix product thoroughly before use. Do not thin. Use directly as supplied. If thinning is necessary use clean water. Apply when surface and air temperatures are above 50 Deg. F. Coverage will depend on texture and porosity of the substrate. SHUTTER COAT is designed for spray application.

CLEAN UP:

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

COVERAGE (THEORETICAL):

Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 200-300 square feet per gallon. Two coats are always recommended for maximum performance.

RECOMMENDED THINNER:

SHUTTER COAT does not require thinning and should be used as is, directly from the container.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An Inseco representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

Finish:	Semi-Gloss & Satin
Pigment Type:	Titanium Dioxide & Inert Pigments
Vehicle Type:	100% Acrylic
Solvent Type:	Water
% Solids By Weight:	53% +/- 2%
% Solids By Volume:	39% +/- 2%
Density:	10.65 lbs. per gallon
Viscosity @ 75 deg. F (24 deg. C):	115 +/- 2 K.U.
VOC:	Less than 150 g/l
Flash Point, Minimum:	Not Flammable
Flame Spread:	Class A rating on non combustible substratum
Estimated Dry Time:	Touch: 15-30 Minutes Recoat: 30-60 Minutes

CAUTION: USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. Wash hands after handling and before eating. Close can when not in use. Keep from freezing.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH approved respirator to control lead exposure. Carefully clean up with a HE PA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



INSECO

INSECO, Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com