

CONCRETE & BRICK

SEAL RX

WATER REPELLENT & DAMP-PROOFER

SEAL Rx CONCRETE & BRICK is a water based solution designed to impart water repellency and stain resistance to a wide variety of concrete and aggregate surfaces. The solution reacts with the carbon dioxide in the air to form an insoluble water-resistant treatment within 24-72 hours after application.



Prevents
Water
Damage

Resists
Stains &
Mildew

Easy to
Apply

Resists
Spalling

RECOMMENDED USES: For properly prepared, uncoated concrete walls, foundations, pre-cast concrete, block, brick and most aggregate surfaces.

SURFACE PREPARATION: Dirt, grease, grime and any foreign material must be removed before application of SEAL Rx CONCRETE & BRICK. Treat surface for mildew. Oil and grease should be scrubbed with a solution of OxiClean and water.

APPLICATION INFORMATION: Apply with brush, roller, airless sprayer or pump sprayer. When spraying, use a tip designed for gloss coatings. Apply when surface and air temperatures are above 32 Deg. F and rising. Do not apply if the threat of rain exists. Do not over apply or allow product to puddle.

- Always apply a test sample to insure compatibility
- Do not apply to a surface that was previously treated with another product
- Take care to cover nearby vegetation, glass, plastic and metals. DP 960 may damage them.
- May be applied to damp surface, however, do not apply when standing water is present

RECOMMENDED THINNER: SEAL Rx CONCRETE & BRICK does not require thinning and should be used as is, directly from the container.

CLEAN UP: Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 200-300 square feet per gallon.

BENEFITS:

- Reduces water absorption into the substrate, thus reducing spalling due to freeze thaw and efflorescence, thereby increasing the life of the substrate.
- Colorless and non-yellowing protection preserves the natural appearance of the substrate.
- Penetrating & breathable
- Low VOC
- May be applied to damp surfaces
- UV Resistant
- Reduces mildew growth on surface

Finish:	Natural
Pigment Type:	None
Solvent Type:	Water
Density:	8.50 lbs. per gallon
Viscosity @ 75 deg. F (24 deg. C):	Waterlike
Coating VOC:	<50 g/l
Flash Point, Minimum:	Not Flammable
Flame Spread:	Class A rating on non combustible substratum
Estimated Dry Time:	Touch: 2 hours Recoat: 30 minutes Foot Traffic: 2 hours Vehicular Traffic: 72 hours

SEAL Rx CONCRETE & BRICK is water based do not allow product to freeze.

CAUTION: KEEP OUT OF REACH OF CHILDREN! WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Technical data contained here in is true and accurate at the date of issue, but is subject to change without notice. An Inseco representative should be contacted with any questions concerning product information or application procedures. Our products conform to Inseco quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.



INSECO

INSECO, Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com