



ENHANCE

SEAL Rx

NATURAL STONE & CONCRETE ENHANCING SEALER

SEAL Rx ENHANCE is a heavy duty, solvent based, silane-siloxane designed to enhance color, impart water repellency and stain resistance to a wide variety of natural stone, concrete and aggregate surfaces. The silanes react chemically and bond with the substrate to form an insoluble water-resistant treatment within 24-72 hours after application.

Enhances
Color

Prevents
Water
Damage

Resists
Stains &
Mildew

Easy to
Apply

RECOMMENDED USES: For properly prepared, unsealed natural stone, concrete walls, foundations, pre-cast concrete, block, brick and most aggregate surfaces.

SURFACE PREPARATION: Dirt, grease, grime and any foreign material must be removed before application of SEAL Rx ENHANCE. Treat surface for mildew. Oil and grease should be scrubbed with a solution of OxiClean and water.

APPLICATION INFORMATION: Apply with pump sprayer, roller, or brush. When spraying, use a tip designed for gloss coatings. Apply when surface and air temperatures are above 32 Deg. F and rising.

Do not apply if the threat of rain exists. Do not over apply or allow product to puddle.

- Always apply a test sample to insure compatibility
- Do not apply to a surface that was previously treated with another product
- Take care to cover nearby vegetation, glass, plastic and metals. Seal Rx ENHANCE may damage them.
- May be applied to damp surface, however, do not apply when standing water is present
- Micro-mop immediately after application of Seal Rx ENHANCE.

RECOMMENDED THINNER: SEAL Rx ENHANCE does not require thinning and should be used as is, directly from the container.

CLEAN UP: Clean up drips and spills immediately using any type of solvent. Clean tools and equipment with any type of solvent.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 600-800 square feet per gallon.

BENEFITS:

- Enhances color of substrate.
- Reduces water absorption into the substrate, thus reducing spalling due to freeze thaw and efflorescence, thereby increasing the life of the substrate.
- Resists staining
- Colorless and non-yellowing protection preserves the appearance of the substrate.
- Penetrating & breathable
- Low VOC
- May be applied to damp surfaces
- UV Resistant
- Reduces mildew growth on surface

ENVIRONMENTAL & SAFETY INFORMATION: Improper handling or use may be hazardous. Recommended safety precautions for storage, handling and application must be observed.

Finish:	Enhanced look
Pigment Type:	None
Solvent Type:	Solvent
Density:	7.0 lbs. per gallon
Viscosity @ 75 deg. F (24 deg. C):	Waterlike
Flame Spread:	Class A rating on non combustible substratum
Estimated Dry Time:	Touch: 2 hours Recoat: 30 minutes Foot Traffic: 2 hours Vehicular Traffic: 72 hours

DANGER: COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN!

Contains flammable solvents. Causes eye burns. Vapor is harmful. May cause allergic skin reaction. Do not get in eyes, on skin or on clothing. Wear eye and skin protective equipment when handling. Wear appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable levels. Follow respirator manufacturer's recommendations for use. Keep containers closed when not in use. **FIRST AID:** In case of eye contact, flush eyes immediately with plenty of fresh water for at least 15 minutes. Call a physician. If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth and seek immediate medical assistance. In case of skin contact, wash immediately with soap and fresh water. Remove contaminated clothing and launder before use. Discard shoes if material has penetrated inside surface.

CAUTION: KEEP OUT OF REACH OF CHILDREN! WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Technical data contained here in is true and accurate at the date of issue, but is subject to change without notice. An Inseco representative should be contacted with any questions concerning product information or application procedures. Our products conform to Inseco quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.



INSECO

INSECO, Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com