



NATURAL

AGGREGATE BINDER

100% ACRYLIC • MULTI SURFACE
LIQUID BONDING AGENT

INSECO's AGGREGATE BINDER Natural is a 100% acrylic liquid bonding agent designed to stabilize decorative rocks, decomposed granite, gravel and mulch. The product binds the aggregate together protecting it and keeping it in place.

Strengthens
Surfaces

Secure
Bonding
Agent

Easy to
Apply

May
Apply to
Damp
Surfaces

Water
Based

RECOMMENDED USES: For use on decorative rocks, decomposed granite, gravel and mulch.

SURFACE PREPARATION: Remove any foreign material before applying new coating. Treat surface for mildew. Surface may be damp but no standing water.

APPLICATION INFORMATION: Apply with your choice of sprayer. Apply when surface and air temperatures are above 50 Deg. F.

DRY TIME: To touch: 30 minutes. Recoat: 1 hour

RECOMMENDED THINNER: AGGREGATE BINDER Natural does not require thinning and should be used as is directly from the container.

CLEAN UP: Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 200 - 300 square feet per gallon.

AGGREGATE BINDER Natural is water based. Do not Freeze.

CAUTION: KEEP OUT OF REACH OF CHILDREN! WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Finish:	Clear
Pigment Type:	None
Vehicle Type:	100% Acrylic
Solvent Type:	Water
% Solids By Weight:	24% +/- 2%
% Solids By Volume:	22% +/- 2%
Density:	8.54 lbs. Per gallon
Viscosity @ 75 deg. F (24 deg. C):	Waterlike
Coating VOC:	< 100 g/l
Flash Point, Minimum:	Not Flammable
Flame Spread:	Class A rating on non combustible substratum
Estimated Dry Time:	Touch: 30 Minutes Recoat: 1 Hours
Recommended Dry Film Thickness Per Coat:	0.05-1.0 Mills DFT.

Technical data contained here in is true and accurate at the date of issue, but is subject to change without notice. An INSECO representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.



INSECO

INSECO, Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com