

WET LOOK

AGGREGATE BINDER

URETHANE LIQUID BONDING AGENT



INSECO's AGGREGATE BINDER Wet Look is a dual component, "wet look", water based urethane designed to stabilize decorative rocks, decomposed granite, gravel and mulch. The product binds the aggregate together protecting it and keeping it in place.

Strengthens Surfaces

Secure Bonding Agent

Easy to Apply

May Apply to Damp Surfaces

Water Based

RECOMMENDED USES: For use on decorative rocks, decomposed granite, gravel and mulch.

SURFACE PREPARATION: Remove any foreign material before applying new coating. Treat surface for mildew. Surface may be damp but no standing water.

MIXING DIRECTIONS: AGGREGATE BINDER Wet Look is supplied as a 2 part system containing 2 gallons of Part A and ½ gallon of Part B. Combine Part A & Part B and mix thoroughly with gentle agitation for 2-3 minutes. Do not whip air into the material. After mixing Part A & Part B add 2 ½ gallons of water to the mixture and stir thoroughly. The mixture is now ready to apply. AGGREGATE BINDER Wet Look has a 2-3 hour pot life once Part A & Part B are combined, therefore, do not mix more than you can apply in that time frame.

APPLICATION INFORMATION: Apply with your choice of sprayer. Apply when surface and air temperatures are above 50°F. When spraying, use a tip designed for gloss coatings. Do not apply if the threat of rain exists or if moisture or dew may condense on the surface prior to curing. Cover and protect all vegetation and surrounding areas not being bound. Do not over apply, soak the substrate or allow product to puddle. Two thin coats are recommended for best performance. A second coat may be applied when the first coat is dry to the touch..

DRY TIME: To touch: 30 minutes. Recoat: 1 hour

CLEAN UP: Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 200 - 300 square feet per gallon.

AGGREGATE BINDER Wet look is water based. Do not Freeze.

Finish:	Clear
Pigment Type:	None
Vehicle Type:	Urethane
Solvent Type:	Water
% Solids By Weight:	50% +/- 2%
% Solids By Volume:	48% +/- 2%
Density:	8.54 lbs. Per gallon
Viscosity @ 75 deg. F (24 deg. C):	Waterlike
Coating VOC:	< 100 g/l
Flash Point, Minimum:	Not Flammable
Flame Spread:	Class A rating on non combustible substratum
Estimated Dry Time:	Touch: 30 Minutes Recoat: 1 Hours
Recommended Dry Film Thickness Per Coat:	0.05-1.0 Mills DFT.

CAUTION: KEEP OUT OF REACH OF CHILDREN! WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Technical data contained here in is true and accurate at the date of issue, but is subject to change without notice. An INSECO representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any,



INSECO

INSECO, Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com